

Ci200RS-THX Square / 200 mm KEF

Merk: KEF
Model: SP3927AA

€734,00



SCAN OM TE
BESTELLEN



OMSCHRIJVING

Features KEF's patented Uni-Q driver array

With a 38mm(1.5inch) tweeter voice coil coupled to a vented aluminium dome with tangerine waveguide, and a woofer with absolutely massive magnet and Z-flex surround, the KEF Ci200RS-THX is capable of delivering a magical musical theatre experience even in the largest of rooms.

Ci200RS-THX

For the ultimate Extreme Home Theatre, the Ci-R Series has the outstanding acoustic capabilities of the KEF floorstander it's named after, with all the drama and emotional intensity of full theatre sound quality.

With a 38mm(1.5inch) tweeter voice coil coupled to a vented aluminium dome with tangerine waveguide, and a woofer with absolutely massive magnet and Z-flex surround, the KEF Ci200RS-THX is capable of delivering a magical musical theatre experience even in the largest of rooms.

GRILLE ON

Ci200RS-THX is an in-wall speaker certified to THX ULTRA2 standard. A deep understanding of the filmmaking

Bovenstaande informatie is uitsluitend informatief/indicatief en aan wijziging onderhevig

MA 10u tot 18u30
DI 10u tot 18u30
WOE 10u tot 18u30
DO 10u tot 18u30

VRIJ 10u tot 18u30
ZAT 10u tot 18u
ZON GESLOTEN

process and surround sound is at the very heart of every THX certified 2.1, 5.1 and 7.1 speaker system. Engineered with design characteristics of professional studio speakers, THX recreates the tonal balance of the filmmaker's final mix in your living room. The results? Action sequences are impactful, and dialogue-driven moments are natural and engaging.

THX certified in-wall speakers deliver the appropriate frequency response and high output and imaging quality of a traditional box speaker. This provides the best of both worlds - THX surround sound performance from components that blend harmoniously with any room decor.

SPECIFICATIES

Algemeen		Audio	
Aantal luidsprekers in de doos	1 speaker	Frequentiebereik	33 - 28000 Hz
Type speaker	Inbouw		
Fysieke kenmerken		Luidsprekeropbouw	
Breedte	24 cm	Diameter tweeter	38 mm
Gewicht	3,6 kg	Diameter woofer	200 mm
Hoogte	24 cm	Ingebouwde tweeter	✓
		Ingebouwde woofer	✓
Luidsprekerprestaties			
Aanbevolen versterker vermogen	10 - 190 W		
Gevoeligheid	90 dB		
Impedantie	4 ohm		

Bovenstaande informatie is uitsluitend informatief/indicatief en aan wijziging onderhevig

MA	10u tot 18u30	VRIJ	10u tot 18u30
DI	10u tot 18u30	ZAT	10u tot 18u
WOE	10u tot 18u30	ZON	GESLOTEN
DO	10u tot 18u30		