



SL-1210GEG-K Technics

Merk: Technics
Model: SL-1210GEG-K

€4.499,00



SCAN OM TE
BESTELLEN

OMSCHRIJVING

Coreless Direct Drive Motor

Conventional analogue turntables have problems with degradation in sound quality caused by factors such as minute speed vibration during rotation and rotation irregularity called "cogging." In the SL-1200G, the use of a newly developed coreless direct-drive motor with no iron core eliminates cogging. Also, the twin-rotor construction reduces the bearing load while maintaining high torque and also reduces minute vibration during rotation. These factors enable reproduction of the warm, exquisitely detailed sound etched on analogue records.

High-precision Motor Control Technology

The application of motor control technology developed for Blu-ray devices and switching the drive mode depending on the operational status of the motor achieve a high-starting torque and highspeed stability.

Three-layered Turntable Platter

The turntable has a three-layered construction with a rigidly combined brass and aluminium die-cast platter. With a deadening rubber covering its entire rear surface to eliminate unnecessary resonance, thereby

Bovenstaande informatie is uitsluitend informatief/indicatief en aan wijziging onderhevig

MA 10u tot 18u30
DI 10u tot 18u30
WOE 10u tot 18u30
DO 10u tot 18u30

VRIJ 10u tot 18u30
ZAT 10u tot 18u
ZON GESLOTEN

achieving high rigidity and vibration damping. This delivers smooth rotational stability and inertial mass surpassing the SP-10MK2, the direct-drive turntable standard used by broadcast stations worldwide, as well as having more than twice the inertial mass of the SL-1200MK5.

High-level Balance Adjustment

When the weight distribution of the turntable is uneven, excess vibration or noise occurs during rotation, which causes degradation in sound quality. Therefore, the balance of the turntable is adjusted at the factory by using specialized high-precision balance adjustment equipment for each and every item after the turntable is assembled. Turntables that have undergone adjustment are labelled with a sticker reading "BALANCED" to indicate that adjustment has been done.

High-sensitive Tonearm

The tonearm employs lightweight magnesium which has a high damping effect, with cold drawing improving the characteristics of the material and achieving the high-precision required. In addition, high initial-motion sensitivity is attained by employing the traditional Technics gimbal suspension construction with horizontal rotation axis and the vertical rotation axis intersecting at a single central point, as well as high-precision bearings using a cut-processed housing.

Four-layered Cabinet Construction

A hairline-processed, 10-mm-thick top panel of immaculate aluminium has been added to the previous three-layered construction of aluminium die-cast, BMC, and heavyweight-class rubber on the SL-1200MK5. This four-layered construction combines high rigidity with a high-quality finish and feel.

High-quality Terminals

The use of brass-milled, gold-plated phono terminals and ground terminals prevent degradation in sound quality while enabling the easy attaching and detaching of cables. Also the use of metal shielding construction inside the case reduces the effects of external noise.

SPECIFICATIES

Algemeen		Fysieke kenmerken	
Toerental	33 rpm, 45 rpm, 78	Breedte	45,3 cm
platenspeler	rpm	Diepte	37,2 cm

Bovenstaande informatie is uitsluitend informatief/indicatief en aan wijziging onderhevig

MA	10u tot 18u30	VRIJ	10u tot 18u30
DI	10u tot 18u30	ZAT	10u tot 18u
WOE	10u tot 18u30	ZON	GESLOTEN
DO	10u tot 18u30		

Gewicht	18 g
Hoogte	17,3 cm
Kleur	Zwart

Bovenstaande informatie is uitsluitend informatief/indicatief en aan wijziging onderhevig

MA	10u tot 18u30	VRIJ	10u tot 18u30
DI	10u tot 18u30	ZAT	10u tot 18u
WOE	10u tot 18u30	ZON	GESLOTEN
DO	10u tot 18u30		